

## Anticorrosion oils

# FAMCORTIL<sup>®</sup> 235

**FAMCORTIL<sup>®</sup> 235 is protective anticorrosion product manufactured from selectively refined mineral oil, corrosion inhibitors, additives for water displacement as well as components for lubrication, penetration and increase of adhesion to metal surfaces.**

### ADVANTAGES

- After product application, oily, highly adhesive, thin, light brown protective film remains on protected surfaces
- In conditions of increased atmospheric moisture, this film has good protective properties.
- Good ability of water displacement
- Low pour point enables, besides protection, applying this product for the lubrication of protected assemblies and devices also at low temperatures (up to -35°C)

### QUALITY LEVEL

FAM FSP 22802  
ISO-L-RDD

MIL-C-22 235 A

### APPLICATION

**FAMCORTIL<sup>®</sup> 235** is used for anticorrosion protection and lubrication of parts, assemblies and mechanisms. It is also applied for the protection of tools and cold rolled sheet, strips and profiles during indoor storage.

**FAMCORTIL<sup>®</sup> 235** is applied to clean surfaces by immersion, spraying or coating at a wide temperature interval (from -35°C to + 50°C). If the application is done by spraying with a compressor it is necessary to have operating pressure of minimum 4 bar. In case of assemblies and devices, it is not necessary to remove the protective film prior to the assembly process, since it will provide lubrication until the lubricating oil reaches the spot.

### TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	<b>FAMCORTIL<sup>®</sup> 235</b>	METHODS
Flash point	°C	Min.160	SRPS EN ISO 2592
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	Min.40	SRPS ISO 3104
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	Min. 6	SRPS ISO 3104
Pour point	°C	Max.-35	SRPS ISO 3016



#### STORAGE

Store in a confined space. Do not store at elevated temperatures, nor in places exposed to direct sunlight, nor at temperatures below 5°C. All necessary instructions can be found in the Safety Data Sheet. It contains details of possible hazards, warnings and first aid measures, as well as the environmental impact and the necessary measures when storing.

#### PACKING

Plastic canisters of 20 kg and tin drums of 180 kg.

---

**Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.**



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia  
Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008  
[www.fam.rs](http://www.fam.rs)