



## TYPICAL CHARACTERISTICS

Characteristics	Units	Values						Methods
		000	00	0	1	2	3	
FOR®	-	000	00	0	1	2	3	DIN 51 818
Colour	-	green						visual
Soap type/Thickener	-	Lithium soap						-
NLGI grade	-	000	00	0	1	2	3	DIN 51 818
Working penetration at 25°C , 60 cycles	mm/10	455	420	370	320	280	235	SRPS ISO 2137
Dropping point	°C	150	160	175	185	190	190	SRPS ISO 2176
Kinematic viscosity of base oil at 40°C	mm <sup>2</sup> /s	ca 130						SRPS ISO 3104
Oxidation stability,100h/100°C	kPa	30						ASTM D 942
Copper corrosion, 24 h /100°C	degree	1						ASTM D 4048
Water resistance at 90°C	rating	1						DIN 51 807/1
EMCOR test 168 h /dist. water	rating	-				0/0		DIN 51 802
Weld load	N	2500				3150		ASTM D 2596
Temperature of application	°C	-30 to +115				-30 to +120		

## STORAGE

Store in a covered area, protected from direct influence of sun and moisture, away from the ignition source. Recommended storage temperature: - 5°C to +25°C.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

## PACKING

Cans of (0,8, 4 and 20) kg, tin drums of 180 kg

FOR 2EP 50 kg, container and eurocartridge of 0,4kg

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.

